PISARA

Mirror Cabinet installation and care guide

BEFORE YOU START P. 02 INSTALLATION P. 03 ELECTRICAL INSTALLATION P. 06 CARE AND MAINTENANCE P. 07 DIMENSION IMAGES P. 07		
INSTALLATION P. 03 ELECTRICAL INSTALLATION P. 06 CARE AND MAINTENANCE P. 07		
CARE AND MAINTENANCE P. 07	INSTALLATION	P. 03
DIMENSION IMAGES P. 07		
	DIMENSION IMAGES	P. 07

Before you start

Before you start

Read through the installation guide carefully.

Mirror cabinet installation includes the installation of the fixture without plumbing or electrical installation.

Check the bearing capacity of the wall.

If you are unsure about installing the fixtures, please hire a professional installer. All the electrical connections must be installed by professionals. Make sure that mounting fixtures to the wall does not damage the wiring or plumbing inside the wall.

What you need for installation

- · Utility knife or scissors
- · Measuring tape
- · Spirit level
- · Cross-head (Phillips) screwdriver for adjusting the doors
- · Drill machine (if wall plugs are required for proper mounting)
- with percussion (if the fixture is mounted to a brick or concrete wall)
- · Battery machine
 - · Bits that fit the screws
 - · Bit for the pilot hole for mounting the fixture
- Caulking gun
- Vacuum cleaner

What you need for mounting

- Appropriate screws and washers that fit them for mounting the fixture
- · Wall plugs (if required for proper mounting)
- · Sanitary silicone, colourless or matching the fixture

Installation

1. Open the package.

- A Use a utility knife or scissors.
- B Make sure the blade does not hit the fixture.
- C Place the fixture on top of packing cardboard or some other protective surface.

Check the fixture for possible transport damage or factory defects

A If you notice something, report it to the seller before installing the fixture. Note! **Do not install a damaged fixture**.

3. Remove the mirror doors.

- A Support the door during its removal.
- B Remove the hinges starting from the bottom, removing the top hinge last.
 - The hinge comes off when you pull the lever at the rear end of the hinge arm away from the frame.
- C Lower the door on a protective cover and leave it to the side to wait.

4. Measure the desired position of the mirror cabinet.

- A Measure the position of the wedge strip on the wall (measuring instructions in the dimension image).
- B Mark the locations for the pilot holes on the wall.
- C Check that the possible power supply comes into the top case.









Installation

5. Fix the wedge strip on the wall.

- A If wall plugs are required for proper mounting, drill the holes you need in the wall where you have marked the pilot holes and install the wall plugs.
 - All **Tip:** To ensure a neat outcome, use a vacuum cleaner while drilling and finish off by vacuuming the hole you have drilled.
- B Use a spirit level to make sure the wedge strip is level and adjust if necessary.
- **6.** Clean up after the installation and remove any drill dust.

7. Mount the fixture in position.

- A If you have ordered bottom lights, check that the wire for the lights comes inside the top case.
- B Lift the fixture in position from the top so that the counterpart for the wedge strip is set in the wedge strip.
- C Check the lateral position of the fixture and adjust if necessary.
- D **Tip:** If there is an electrician available, after the mirror cabinet has been installed is a good time for any electrical installations. Separate instructions for electrical installations are provided after the steps of the installation guide.
- E Place the top panel in its position..















Installation

8. Install the glass shelves.

- A Place the shelf supports in the desired heights, 4 supports per shelf.
- B Holding the shelf horizontal, first lower one side on top of the supports and then the other.

9. Install the mirror doors.

- A Support the door during the installation.
- B Install the hinges starting from the top, installing the bottom hinge last.
 - Install the hinge by first pushing the front end of the hinge arm onto the backplate, then the rear end, until you hear a click.
- C Check to make sure the door works.

10. Check the position of the mirror doors and adjust, if necessary.

- A Mirror door adjustments must always be made very gradually and both hinges must be adjusted evenly otherwise one hinge may become twisted and, at worst, come loose from the mirror.
- B Height adjustment
 - Loosen the tightening screws in the backplates of the hinges so that the backplates can move, but are not completely loose.
 - B2 Adjust the height by lifting or lowering the door.
 - B3 Tighten the tightening screws.
- C Side adjustment
 - Adjust the lateral position of the door using the frontmost screw of the hinge arms.
- D Depth adjustment
 - Adjust the depth of the door using the rearmost screw of the hinge arms.
- E **Tip:** The hinge we use is Grass Mirro with integrated soft-close.
- **11.** Finish off by cleaning the fixture and removing any stains according to the care instructions.

Congratulations, your installation is now complete!











Electrical installation

- 1. If you want, you can remove the mirror doors before electrical work.
 - A The instructions for removing the doors can be found in the installation guide.
- 2. Remove the top panel to access the top case.
- **3.** If it is necessary to make a cut-out in the structure for electrical wires, this cut-out must be carefully protected from moisture with sanitary silicone.
 - A Before making the cut-out, make sure that the wires will not come into contact with shelves, hinges or other interior structures.
- **4.** Attach the transformer to the bottom of the top panel with the double-sided tape provided.
- 5. Electrical connections to the transformer
 - A Connect the transformer to the mains.
 - B Connect the top and/or bottom lights to the transformer.
- **6.** Connect the plug to the mains.
- **7.** Place the top panel in its position.
- **8.** Finally, reinstall the mirror doors.
 - A The instructions for installing mirror doors can be found in the installation guide.

Care and mainte-nance

1. Cleaning the fixture

- A The fixture and the basin are cleaned using a mild household cleaning agent.
- B They can be cleaned with a slightly damp towel or a microfibre cloth.

2. Instructions for removing stains

- A Any stains on the fixture or the basin should be removed preferably using a household cleaning agent. Remove any stains as soon as you discover them.
- B If the stain cannot be removed with a stain remover, you can use white spirit (turpentine).
 - B1 If you do use white spirit, clean the spot afterwards with a cleaning agent.
 - B2 Using acetone to remove stains from the fixture is prohibited.
- C Stains can be removed using a microfibre cloth or a sponge.

3. Cleaning the mirror doors and glass shelves

- A The mirror doors and glass shelves are cleaned with a glass and mirror cleaning spray or a solution of water and vinegar (one part water, one part vinegar).
- B You can use a cleaning cloth or strong paper towels.
- C **Tip:** Finish off by drying the mirror doors with a window squeegee to avoid streaks.
- 4. The fixture does not require any special maintenance apart from cleaning.

Dimension images

Please download dimension drawings / images from pisarafinland.fi.

Customer service > Documentation

FOR MORE INFORMATION: